



GENEVA SCIENTIFIC
LAB EQUIPMENT SOLUTIONS

DROSOPHILA CHAMBER - DR-36NL



| | |
|---------------------------------|-----------------------|
| Model | DR-36NL |
| Exterior Dimensions (WxDxH) | 33.5" x 33.6" x 77.2" |
| Temp. Range (w/ lights on) | 2-44±0.5 |
| Interior Space | 29.7 cu.ft. |
| Total Shelving Floor Area | 32.3 sq.ft. |
| Maximum Growing Height | 8" |
| Light Intensity (6" from lamps) | No Light |
| Number of Tiers | 6 |

Applications

- *This incubator has a specific combination of features optimized for Drosophila melanogaster
- *Many other applications exist for this product

Percival's IntellusUltra Controller

*Percival Scientific has built a reputation of providing flexible, customized options for research scientists around the world. We have taken the philosophy to the next level with our improved IntellusUltra Controller. Now choose from the levels of functionality that meet your needs.

Lighting System

- *No lights are contained inside the chamber

Cabinet Construction

- *26-gauge smooth galvanized white side walls and top reinforced with 24-gauge backer plates
- *Interior floor constructed of 24-gauge #304-4 stainless steel
- *24-gauge smooth white galvanized exterior
- *NSF compliant seam design
- *Overall wall thickness 2"

Cabinet Construction cont.

- *Foamed-in-place non-CFC insulation
- *One 1¼" diameter access port on right hand wall
- *Chamber floor equipped with floor drain and hose assembly
- *Contains casters assembly and adjustable leveling legs to compensate for floor unevenness in the lab

Insulation

- *Woodless construction using 2" thick foamed-in-place non-CFC Urethane insulation with 93% closed cell, R-value of 12.5, K-value of 0.16 and density of 2.2 lbs/ft³

Doors

- *One door opening of 29.3" x 57.5" providing full access to chamber interior (magnetic gasket provides a tight seal to door frame)

Interior Space

- *29.7 cu.ft. with work area of 32.3 sq.ft. provided on six tiers

Shelving

- *Six tiers of white epoxy coated steel wire shelving (each shelf is 27"D x 28.7"W)

DROSOPHILA CHAMBER - DR-36NL

Shelving cont.

- *Shelves are supported by shelf clips allowing ½" vertical adjustments
- *Maximum clearance between shelves is 8" per tier with all six shelves installed (and the water pan humidifier as standard)

Finish

- *Interior and exterior painted with high reflective, environmentally friendly, high temperature baked white powder coating

Refrigeration

- *Self-contained air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and close temperature control (this continuous running condensing unit ensures precise temperature control by alternating cycling refrigerant and hot gas to coil; this also prolongs life of compressor, and eliminates risk of ice build up in coil)
- *Top mounted refrigeration system allows easy access for maintenance (e.g. cleaning)
- *As heat is rejected, it rises and is dissipated into the room without having any effect on inside temperature of cabinet
- *Solenoid valves have extended stem for quiet and long life operation
- *Ceiling mounted evaporator coils incorporate twin air circulation fans in aluminum housing (heat rejection to ambient with standard chamber: 2504 BTU/hr)
- *Coil is phenolic coated to prolong the life of chamber from the acidic environment that can be created by drosophila

Temperature Range

- *2-44C (+/- 0.5C)

Temperature Safety Limit Controls

- *Experiment Protection: Adjustable high and low temperature controls, audible alarms, and visual indicators provided
- *Controls shut down all power to chamber, activating alarms (when the temperature returns to the normal range the system will automatically reset)

Humidity Control

- *Additive humidity control of higher than ambient to 85% ($\pm 10\%$) lights on for set temperatures between 15° to 30°C
- *Humidity control of higher than ambient to 90% ($\pm 10\%$) lights off for set temperatures between 15° to 30°C
- *Humidity system requires a de-mineralized water supply line which terminates to a 1/2" MPT connector

Electrical Requirements

- *Consult Geneva Scientific for electrical requirements and amperage draw.

Options

- *Dehumidifier with Sensor
- *IntellusUltra Connect
- *CO2 Enrichment Package
- *Self-Contained Water-Cooled Condensing Unit
- *Dry Alarm Contacts
- *Convenience receptacles



GENEVA SCIENTIFIC
LAB EQUIPMENT SOLUTIONS



Geneva Scientific LLC
P.O. Box 408
Fontana, WI 53125

1-877-436-3827
Fax: 262-607-6497
Sales@Geneva-Scientific.com

Specifications are subject to change without notice.
rev. 03/22