



GENEVA SCIENTIFIC

LAB EQUIPMENT SOLUTIONS

DROSOPHILA CHAMBER - DR-36VL



Model	DR-36VL
Exterior Dimensions (WxDxH)	33.5" x 33.6" x 77.2"
Temp. Range (w/ lights on)	5-44±0.5
Interior Space	29.7 cu.ft.
Total Shelving Floor Area	27 sq.ft.
Maximum Growing Height	9.5"
Light Intensity (6" from lamps)	120 micromoles/m ² /sec
Number of Tiers	5

Applications

- *Designed especially for drosophila rearing
- *Many other applications exist for this product

Percival's IntellusUltra Controller

*Percival Scientific has built a reputation of providing flexible, customized options for research scientists around the world. We have taken the philosophy to the next level with our improved IntellusUltra Controller. Now choose from the levels of functionality that meet your needs.

IncuWhite LED lighting system

- *Linear LEDs vertically mounted
- *Intensity programmable up to 120 μ moles/m²/s of light irradiance measured @ 6" from LEDs
- *Programming and control of the lighting is done via IntellusUltra real time controller
- *Dimmable between 5-100% output

Cabinet Construction

- *26-gauge smooth galvanized white side walls and top reinforced with 24-gauge backer plates

Cabinet Construction cont.

- *Interior floor constructed of 24-gauge #304-4 stainless steel
- *24-gauge smooth white galvanized exterior
- *NSF compliant seam design
- *Overall wall thickness 2"
- *Foamed-in-place non-CFC insulation
- *One 1¼" diameter access port on right hand wall
- *Chamber floor equipped with floor drain and hose assembly
- *Contains casters assembly and adjustable leveling legs to compensate for floor unevenness in the lab

Insulation

- *Woodless construction using CFC free insulation (overall wall thickness is 2", ample insulation for maintenance of stated temperature range)

Door

- *One door opening of 29.3" x 57.5" providing full access to chamber interior (magnetic gasket provides a tight seal to door frame)

Interior Space

- *29.7 cu.ft. with work area of 27 sq.ft. provided on five tiers

DROSOPHILA CHAMBER - DR-36VL

Shelving

- *Five tiers of white epoxy coated steel wire shelving (each shelf is 27"D x 28.8"W)
- *Shelves are supported by shelf clips allowing 1/2" vertical adjustments
- *Maximum clearance between shelves is 9.5" per tier with all five shelves installed (and the water pan humidifier as standard)

Finish

- *Interior and exterior painted with high reflective, environmentally friendly, high temperature baked white powder coating

Refrigeration

- *Self-contained air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and close temperature control (this continuous running condensing unit ensures precise temperature control by alternating cycling refrigerant and hot gas to coil; this also prolongs life of compressor, and eliminates risk of ice build up in coil)
- *Top mounted refrigeration system allows easy access for maintenance (e.g. cleaning)
- *As heat is rejected, it rises and is dissipated into the room without having any effect on inside temperature of cabinet
- *Solenoid valves have extended stem for quiet and long life operation
- *Ceiling mounted evaporator coils incorporate twin air circulation fans in aluminum housing (heat rejection to ambient with standard chamber: 2169 BTU/hr)
- *Coil is phenolic coated to prolong the life of chamber from the acidic environment that can be created by drosophila

Temperature Range

- *5°-44°C ($\pm 0.5^\circ\text{C}$) lights on and 2°-44°C ($\pm 0.5^\circ\text{C}$) lights off

Temperature Safety Limit Controls

- *Experiment Protection: Adjustable high and low temperature controls, audible alarms, and visual indicators provided
- *Controls shut down all power to chamber, activating alarms (when the temperature returns to the normal range the system will automatically reset)

Humidity Control

- *Additive humidity control of higher than ambient to 85% (+/-10%) lights on for set temperatures between 15° to 30°C
- *Humidity control of higher than ambient to 90% (+/-10%) lights off for set temperatures between 15° to 30°C
- *Humidity system requires a de-mineralized water supply line which terminates to a 1/2" MPT connector

Electrical Requirements

- *Consult Geneva Scientific for electrical requirements and amperage draw.

Popular options

- *Dehumidifier with Sensor
- *IntellusUltra Connect
- *CO2 Enrichment Package
- *Self-Contained Water-Cooled Condensing Unit
- *Dry Alarm Contacts
- *Convenience Receptacles



GENEVA SCIENTIFIC
LAB EQUIPMENT SOLUTIONS

