



GENEVA SCIENTIFIC

LAB EQUIPMENT SOLUTIONS

TISSUE CULTURE CHAMBER - CU-36L5



Model	CU-36L5
Exterior Dimensions (WxDxH)	33.5" x 33.6" x 77.2"
Temp. Range (w/ lights on)	10-44C +/- 0.5C
Interior Space	29.7 cu.ft.
Total Shelving Floor Area	27 sq.ft.
Maximum Growing Height	5.3"
Light Intensity (6" from lamps)	155 micromoles/m2/sec
Number of Tiers	5

Applications

- *Specifically designed for plant cell culture
- *Unique design of air diffuser with slow vertical airflow, fixed lampbank and slide-out shelves helps to eliminate condensation on Petri dish lids
- *Many other applications exist for this product

Percival's IntellusUltra Controller

*Percival Scientific has built a reputation of providing flexible, customized options for research scientists around the world. We have taken the philosophy to the next level with our improved IntellusUltra Controller. Now choose from the levels of functionality that meet your needs.

Lighting System

- *Each tier of shelves is lighted by cool white fluorescent lamps properly spaced for uniform light intensity over entire shelf
- *Intensity programmable up to 155 micromoles/m2/sec of light irradiance measured at 5" from lamps on 2 on/off light events
- *Programming and control of the lighting is done via IntellusUltra real time controller

Airflow/Circulation

- *Conditioned air circulates through a rear wall duct and is picked up by a specially designed fixed air diffuser located at the bottom of each tier (air is then delivered vertically upward at a slow speed through each shelf)
- *Air diffuser insulates shelf level experiments from heat generated by underlying light fixture (this design minimizes condensation on dish lids)

Cabinet Construction

- *Interior constructed of 22-gauge electro-zinc plated steel
- *Exterior constructed of 18-gauge exterior electro-zinc plated steel
- *Welded seams and joints on outer and inner shells
- *Inner shell supported by non-compressing/non-thermal conducting material locking inner liner in place without a metal-to-metal bond to outer case
- *Chamber is completely self-contained
- *Overall wall thickness is 2"
- *One 1 1/4" diameter access port on R.H. wall
- *Chamber floor equipped with floor drain and hose assembly
- *Contains caster assembly and adjustable leveling legs to compensate for floor unevenness in the lab

TISSUE CULTURE CHAMBER - CU-36L5

Insulation

*Woodless construction using CFC free insulation (overall wall thickness is 2", ample insulation for maintenance of stated temperature range)

Door

*One door opening of 29.2" x 57.5" providing full access to chamber interior (magnetic gasket provides a tight seal to door frame)

Interior Space

*29.7 cu.ft. with work area of 27 sq.ft. provided on five shelves

Shelving

*Five tiers of white epoxy coated steel wire shelving (each shelf is 27"D x 28.8"W)

*Shelves side in and out easily on stainless steel rail assemblies

*Maximum growing height is 5.3"

Finish

*Interior and exterior painted with high reflective, environmentally friendly, high temperature baked white powder coating

Temperature Range

*10-44C (+/- 0.5C) with lights on and 2-44C (+/- 0.5C) with lights off

Refrigeration

*Self-contained air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and close temperature control (this continuous running condensing unit ensures precise temperature control by alternating cycling refrigerant and hot gas to coil; this also prolongs life of compressor, and eliminates risk of ice build up in coil)

*Solenoid valves have extended stem for quiet and long life operation

*Ceiling mounted evaporator coils incorporate twin air circulation fans in aluminum housing (heat rejection to ambient with standard chamber: 3800 BTU/hr)

Temperature Safety Limit Controls

*Experiment Protection: Adjustable high and low temperature controls, audible alarms, and visual indicators provided

*Controls shut down all power to chamber, activating alarms (when the temperature returns to the normal range the system will automatically reset)

Convenience Receptacles

*Two 115/1/60 convenience receptacles provided inside chamber

Electrical Requirements

*Consult Geneva Scientific for electrical requirements and amperage draw.

Options

*Additive Humidity Control with Sensor

*Dehumidifier with Sensor

*IntellusUltra Connect

*Android-Based Touch Screen

*CO2 Enrichment Package

*Self-Contained Water-Cooled Condensing Unit

*Dry Alarm Contacts

*Dimmable Lighting

*LED Lighting in Lieu of Fluorescent Lamps



GENEVA SCIENTIFIC
LAB EQUIPMENT SOLUTIONS

