



GENEVA SCIENTIFIC
LAB EQUIPMENT SOLUTIONS

TISSUE CULTURE CHAMBER - CU-36L6



Model	CU-36L6
Exterior Dimensions (WxDxH)	33.5" x 33.6" x 77.2"
Temp. Range (w/ lights on)	10-44C +/- 0.5C
Interior Space	29.7 cu.ft.
Total Shelving Floor Area	32.3 sq.ft.
Maximum Growing Height	3.6"
Light Intensity (6" from lamps)	350 micromoles/m2/sec
Number of Tiers	6

Applications

- *This chamber is specifically designed for tissue culture on plates/dishes or in flasks
- *Many other applications exist for this product

Percival's IntellusUltra Controller

- *The IntellusUltra control system was purpose-built for controlled environments and is standard on all Percival chambers.
- *Robust and reliable, industrial-grade integrated hardware design
- *Highly flexible architecture facilitates configuration, expansion and customization
- *Precise, simultaneous control of up to 7 environmental parameters
- *Industry-leading experiment protection and system diagnostics

SciWhite LED Lighting System

- *Five tiers of lighted shelving, lit by SciWhite LEDs
- *Intensity programmable up to 350 μ moles/m2/s of light irradiance measured @ 6" from LEDs

SciWhite LED Lighting System (cont.)

- *Programming and control of the lighting is done via IntellusUltra real time controller
- *Dimmable between 10-100% output

Airflow/Circulation

- *Conditioned air circulates through a rear wall duct and is picked up by a specially designed fixed air diffuser located at the bottom of each tier (air is then delivered vertically upward at a slow speed through each shelf)
- *Air diffuser insulates shelf level experiments from heat generated by underlying light fixture (this design minimizes condensation on dish lids)

Cabinet Construction

- *Interior constructed of 26-gauge galvanized steel
- *Interior floor constructed of 24-gauge polished stainless steel
- *Exterior constructed of 24-gauge Galvannealed extra-smooth steel
- *NSF-compliant seam design
- *Overall wall thickness is 2" (5.1 cm)
- *Integrated floor drain
- *Contains casters assembly and adjustable leveling legs
- *One 1.25" access port with air-tight plug
- *Highly durable and reflective coating

TISSUE CULTURE CHAMBER - CU-36L6

Insulation

*Woodless construction using CFC free insulation (overall wall thickness is 2", ample insulation for maintenance of stated temperature range)

Door

*One door opening of 29.3" x 57.5" providing full access to chamber interior (magnetic gasket provides a tight seal to door frame)

Interior Space

*29.7 cu.ft. with work area of 32.3 sq.ft. provided on six shelves

Shelving

*Six tiers of white epoxy coated steel wire shelving (each shelf is 27"D x 28.8"W)

*Shelves side in and out easily on stainless steel rail assemblies

*Maximum growing height is 3.6"

Temperature Range

*10°-44°C (±0.5°C) lights on and 2°-44°C (±0.5°C) lights off

Refrigeration

*Top mounted air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and tight temperature control. Continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; also prolongs compressor life, and eliminates risk of ice build up in coil.

*Extended stem solenoid valves for quiet and long life operation

*Ceiling mounted evaporator coil incorporates twin air circulation fans in aluminum housing (heat rejection to ambient [standard chamber] = BTU/hr.)

Temperature Safety Limit Controls

*Experiment Protection: Adjustable high and low temperature controls, audible alarms, and visual indicators provided

*Controls shut down all power to chamber, activating alarms (when the temperature returns to the normal range the system will automatically reset)

Electrical Requirements

*Consult Geneva Scientific for electrical requirements and amperage draw.

Regulatory Standards

*Electrical Safety: UL-508A, certified and labelled by Percival Scientific under UL file number E340161

*Quality System: ISO 9001:2015, certified under DQS, Inc. under certification number 10017261

Options

*Additive Humidity Control with Sensor

*Dehumidifier with Sensor

*IntellusUltra Connect

*Android-Based Touch Screen

*CO2 Enrichment Package

*Self-Contained Water-Cooled Condensing Unit

*Dry Alarm Contacts

*LED Lighting in Lieu of Fluorescent Lamps



GENEVA SCIENTIFIC
LAB EQUIPMENT SOLUTIONS



Geneva Scientific LLC
P.O. Box 408
Fontana, WI 53125

1-877-436-3827
Fax: 262-607-6497
Sales@Geneva-Scientific.com

Specifications are subject to change without notice.
rev. 01/22